

TCR SHORT ACTION SERIES TACTICAL COMPETITION RIFLE



THE TCR SHORT ACTION SERIES TACTICAL COMPETITION RIFLES ARE ENGINEERED AND DESIGNED TO PROVIDE users with a versatile rifle platform in .223 Remington, .260 Remington, 6.5 Creedmoor, and .308 Winchester calibers. This precision tactical rifle is proudly manufactured in the USA and built on the strong Surgeon RSR bolt action receiver, and the patented SABER®-FORSST® MOD-0 modular rifle chassis. TCR Short Action rifles are available in the A3 configuration accepting either a 5 or 10rd magazine.

TCR's are barreled with Pinnacle Series 416 stainless steel fluted barrels that are safety and performance engineered using APO's proprietary B.A.S.E.D. barrel engineering software. A TCR Pinnacle Series barrel is finished with an 11 degree target crown.

TCR muzzles can be optionally threaded and provided with a Muzzle Thread Protector making TCR Short Actions in .223 and .308 eligible for U.S. F-TR competitive events. TCR's uses a premium tactical two-stage trigger set to 3.5 lbs for a smooth take up, and crisp let off for precise sub-MOA shot placement.

TCR rifles feature an ergonomic MOD-O Quattro carbon fiber forend that is comfortable in the off-hand shooting position and reduces heat mirage. Additionally the forend has 12 o'clock and 6 o'clock MIL-STD 1913 accessory rail locations that accommodate "clip-on" night vision devices and re-positionable bipods.

The fixed SABER HTA ergonomic shoulder stock has tooled adjustments for length of pull, cheek-piece height, and vertical recoil pad placement. The Butt Hook rounds out the shoulder stocks functional design for precision shooting, and a versatile multi-position adjustable field monopod is an available option. TCR rifles have flush cup sling swivel attachment points along the length of the precision rifle.



Ashbury Precision Ordnance Mfg.
A Division of Ashbury International Group, Inc.
PO Box 8024, Charlottesville, VA. 22906-8024
Tel 434-296-8600, Fax 434-296-9260
info@AshburyPrecisionOrdnance.com



AshburyPrecisionOrdnance.com

* Specifications are subject to change.

TCR

SHORT ACTION SERIES

TACTICAL COMPETITION RIFLE



Specifications

Caliber

- .308Win, 6.5 Creedmoor, .260 Remington, .223 Remington

Action

- Surgeon RSR Repeater

Chassis

- SABER SSA-A3

Shoulder Stock

- Fixed HTA w/Tooled Ergonomic Adjustments

Barrel

- Rock Creek Pinnacle™ Series 416R SS 5R barrels
.223 Rem – 22" barrel - 1-in-8 twist
.260 Rem – 24" barrel – 1-in-9 twist
6.5 Crd – 24" barrel – 1-in-8 twist
.308 Win – 20" barrel – 1-in-10 twist

Muzzle Brake

- Optional

Trigger

- Huber Tactical Two Stage trigger set to approx. 3.5 lbs.

Forend

- Quattro Carbon Fiber Forend

Scope Rail

- 20 MOA MIL-STD 1913

Accessory Rail

- 4" Top and Bottom Accessory Rails

Magazines

- A3 10rd detachable box magazine (one supplied)

Hand Grip

- Magpul M1AD grip set

Grip Angle Adaptors

- 17.5° Standard (11° and 27° optional)

Surface Coatings

- MIL-STD 810G corrosion resistant coatings that are dull and non-reflective

Color

- Black w/Black Carbon Fiber Forend. Optional colors Flat Dark Earth, Nordic Gray and OD Green

Accuracy

- <1 MOA or better accuracy with Match grade ammunition

Weight

- Basic Rifle Weights (approx.)
TCR308 12lbs
TCR6.5 12lbs
TCR260 12lbs
TCR223 11lbs

Accessories:

- SABER EO Scope Rings
4-Screw Top 30/34/35mm Rings
- Monopod
- Long Range Accuracy Bipod

TCR300 with Leupold Mk 4 4.5-14x50mm day optical day sight, custom 4" side and 12" bottom accessory rail on Rifle Pack Mat Drag Bag



TCR with 4-16x50mm day optical sight and Long Range Accuracy F-Class Competition bipod

Ashbury Precision Ordnance Mfg.

A Division of Ashbury International Group, Inc.
PO Box 8024, Charlottesville, VA. 22906-8024
Tel 434-296-8600, Fax 434-296-9260
info@AshburyPrecisionOrdnance.com



AshburyPrecisionOrdnance.com

* Specifications are subject to change.