

99

T N -BER®

SABER[®] M700TM-308TR BALLISTICS 21 Accessories

SABER-M700-308TR.com

EXTERNAL BALLISTICS

Bullet Weight: 175gr Ballistic Coefficient: 0.547 (G1) Rifle: SABER M700- 308TR 20" BBL	.308 Winchester BTHP Open Tip Match 2600± Feet Per Second	Caliber: Bullet Type: Velocity:	Station Pressure: 29.53 in. Hg. Humidity: 78% Temperature: 59° Elevation: 0ft ASL	Station Pressur Humidity: Temperature: Elevation:
	-			
1107	12.8	44.25	1006	1100
1197	10.7	36.75	914	1000
1307	8.8	30.00	823	006
1428	7.1	24.25	732	800
1555	5.6	19.25	640	700
1688	4.2	14.50	549	600
1826	3.1	10.50	457	500
1970	2.0	7.00	366	400
2120	1.1	3.75	271	300
2274	0.4	1.25	183	200
2434	0	0	91	100
FPS	MILS	MOA	Meters	Yards
n Velocity	Elevation	Elevation	Distance	Dist
	s .54/BC	.308 Winchester 1/5gr Match 2600tps .54/BC	hester 1/5g	.308 Winc

ACCESSORIES

TACTICAL RIFLE SYSTEM

- Bipod Premium Rifle Scopes
 SABER EO Scope Rings
 Monopod, 3-Position Adjustable

- Sling Shooting / Carry
 Sound Suppressor
 Precision Rifle Cleaning Kit
 Protective Padded Nylon Field Bag
 Hard Transit Case Custom
- Foam Interior
- Ballistic Software & Hand-held Computer

Rifle Packages,

Ma

- Ballistic Calculator .308Win Analog (no batteries required)
 Magazines, Box 5 & 10rd Capacity
 SABER Field Multi-Tool Anti-Cant Device, Scope Mounted
 Angle Cosine Indicator (ACI)
 Spare Fasteners Package
 Armorer Repair Parts Kit
 Sniper's Field Tool Kit

- Observation Spotting Scope / TACT 3 Compact Tripod Kit
- RSTA-II Tripod Shooting System

COATINGS & FINISHES











Ashbury Precision Ordnance Mfg. • 84 Business Park Circle • Ruckersville • Virginia • 22968 • 434-296-8600 AshburyPrecisionOrdnance.com • info@AshburyPrecisionOrdnance.com M700 is a trademark and used with the authorization of RA Brands, L.L.C.

v20190204



SABER[®] M700[™]-308TR

SABER-M700-308TR.com

TACTICAL RIFLE SYSTEM

Ashbury Precision Ordnance's SABER M700 Tactical Rifle is the operational standard for intermediate to long range tactical rifle platforms. The SABER M700 Tactical Rifle is designed to provide shooters with an accurate and ergonomically adjustable tactical rifle designed for reliable service under tough conditions in the field or on the range. Chambered for the versatile .308 Winchester cartridge, the SABER M700 Tactical Rifle provides long range shooters with reliable sub-MOA precision out to distances of 1,000 yards.

Designed for accuracy and dependability in the field, the SABER M700 Tactical Rifle provides shooters with many quality features. *The Action:* Remington's proven Model 700 bolt action receiver manufactured from quality carbon steel, accurized by experienced APO Precision Weapon Section gunsmiths & coated with a tough, corrosion-resistant Cerakote ceramic finish. *The Barrel:* Hammer forged carbon steel - medium-heavy contour - threaded muzzle & highly efficient muzzle brake suppressor adapter. *The Trigger:* Reliable, adjustable single-stage trigger that breaks cleanly and crisply at 3 lbs.

The Patented Rifle Chassis: The SABER M700 Tactical Rifle is built on Ashbury's ergonomically adjustable MRCS-*AR* MOD-1 modular rifle chassis system. SABER rifle chassis are rugged, reconfigurable, require no bedding to obtain optimal accuracy and are impervious to hot and cold weather conditions. **The Ergonomic Shoulder Stock:** The SABER M700 Tactical Rifle features the PBA-H (Push Button Adjustable Hybrid) with length of pull, vertical recoil pad drop and thumbscrew cheek piece height adjustments. Stock adjustments are *completely tool-less* and positive locking! The PBA-H shoulder stock is fitted with a butt hook as standard equipment for non-shooting hand support and a rapidly adjustable 3-position field monopod is available as a user-installable option.

SABER modular rifle chassis feature a user-adjustable hand grip, to change distance-to-trigger (for large and small hands) with a comfortable 11° grip angle. Optional hand grips and grip angles are available. The SABER M700 Tactical Rifle is fitted with an ambidextrous paddle lever magazine catch-release and comes with one 10 round AICS patterned magazine.

The SABER M700 Tactical Rifle's AR-08 aluminum alloy MOD-1 forend has a unique octagonal design with M-LOK[®] accessory rail mounting locations at 3, 6, 9 and 12 o'clock positions. The SABER M700 Tactical Rifle additionally features Ashbury's patented, continuous one-piece MIL-STD 1913 20 MOA unitized monolithic top rail that provides structural rigidity for long range accuracy, secure in-line mounting of the rifle scope, and clip-on night vision or thermal imager device. Shoot-ability, comfort, ergonomic adjustability, modularity, and low-felt recoil with sub-MOA accuracy are hallmarks of the SABER M700 Tactical Rifle.







CALIBER

.308 Winchester (optional 6.5 Creedmoor)

ACTION

APO Accurized Remington Model 700® *AAC-SD*[™] Short Action Receiver, Carbon Steel, Cerakote Armor Black Finish

BOLT

Two-Lug Bolt Design (optional one piece bolt with Mini-16 Extractor and Tactical Bolt Knob)

TRIGGER

Single-Stage Adjustable Enclosed Body (set to 3 lbs.; optional 2-stage)

BARREL

- .308 20" Hammer Forged Carbon Steel, 1:10 Twist, Muzzle Threaded ¾-24
- 6.5CM 22" Hammer Forged Carbon Steel,1:8 Twist, Muzzle Threaded %-24

MUZZLE BRAKE AAC Blackout 51T (alternate manufacturer and models available)

SOUND SUPPRESSOR (optional) AAC 762SD (alternate manufacturer and models available)

RIFLE CHASSIS - MODULAR

SABER RSA-A3 MRCS-AR MOD-1

SHOULDER STOCK - ERGONOMIC/ADJUSTABLE

- PBA-H Push Button Adjustable Hybrid, Tool-less Positive Locking
- Limbsaver Premium Recoil Pad
 Butt Hook, Interchangeable
- Flush Cup Sling Swivel Sockets x2
 Monopod, 3-Position (optional)

STOCK INTERFACE

Double Locking Alloy Folding Hinge, Tension Adjustable (optional Fixed & Locking Stainless Steel)

MAGAZINE - BOX

10rd Detachable AICS Patterned (x1) (optional 5/10rd Polymer Mags)

HAND GRIP

Ergo Grip Slimline (Changeable AR-15/M-16 Style)

GRIP ANGLE ADAPTERS

11° (optional 17.5° and 27°)

FOREND

- AR-08 Octagonal Aluminum Alloy M-LOK[®] Accessory Mounting Locations at 3-6-9-12 o'clock Positions
- M-LOK Flushcup Socket (x1)

MONOLITHIC PICATINNY SCOPE RAIL

20 MOA Slant, MIL-STD 1913, Co-Linear Mounted Day & Night Optics

ACCESSORY RAILS

- M-LOK Picatinny Accessory Rails (optional)
- M-LOK Accessories Kit (optional)

SURFACE COATINGS

Hard Coat Anodized and Cerakote Coating

COLOR

- SABER Chassis: Black MIL -A-8625 Type III Hard Coat Anodized
- Barreled Action: Armor Black

ACCURACY

¾ MOA with Match-Grade Ammunition

PACKAGING

- Heavy Duty Corrugated Shipping Container
- Hard Lockable Transit Case with Custom Foam Interior (optional)
- Nylon padded Field Carry Bag (optional)

BASE RIFLE WEIGHT & DIMENSIONS

.308Win - 11.3 lbs. / Extended Length 41" / Folded Length 31.5" (approx) .6.5CM - 11.5 lbs. / Extended Length 43" / Folded Length 33.5" (approx) Specifications are Subject to Change. Custom Configurations Available.