

**APO**  
ASHBURY PRECISION ORDNANCE<sup>®</sup>  
The Precision Long Range Rifle Specialists



**SPR-308**

INTERMEDIATE RANGE

**SABER PRECISION RIFLE - TACTICAL SYSTEM**

Patented Modularity by Definition... Precision Engineered by Design



# SPR-308

SABER-Precision-Rifle.com

SABER® Precision Rifle - Tactical System

The SPR-308 SABER® Precision tactical rifle is a rugged and dependable precision rifle manufactured by Ashbury Precision Ordnance. The full featured SPR-308 is designed to provide users with a durable, modular and ergonomically adjustable precision rifle designed for reliable accurate service under tough field conditions. Chambered in .308Win or 7.62 x 51mm, the SPR-308 provides exceptional accuracy and is capable of precision target engagements at distances exceeding 800 meters.

Designed for precision intermediate to long distance shooting in the field, the SPR-308 provides users with many notable operational features. **The Action:** APO's SABER® SX octagonal stainless steel bolt action receiver is precision CNC manufactured to close tolerances with a one-piece bolt crafted of tool steel, finished with a tough Black Nitride coating. **The Barrel:** Pinnacle Series stainless steel – fluted contour - match grade, threaded muzzle, and highly efficient muzzle brake suppressor adapter. **The Trigger:** Adjustable single-stage trigger which breaks crisply at 3 lbs.

**The Patented SABER Chassis:** SABER ASX MOD-1 Alloy Tactical (AL-T) modular rifle chassis system. SABER rifle chassis are rugged, reconfigurable, low maintenance, and require no bedding to deliver optimal accuracy. SABER rifle chassis are impervious to foul weather conditions, and hot/cold temperature extremes. **The Ergonomic Shoulder Stock:** Tool-less ergonomically adjustable PBA-H (Push Button Adjustable Hybrid) shoulder stock. The PBA-H provides push button length of pull, vertical recoil pad position and thumbscrew cheek piece height adjustments - all positive locking and completely tool-less! The PBA-H utilizes a butt hook for non-shooting hand support, and an optional rapidly adjustable 3-position field monopod.

The SPR-308 has a user adjustable hand grip to customize the distance-to-trigger for large and small hands and an interchangeable near vertical 11° grip angle. The SPR-308 is fitted with an ambidextrous paddle lever magazine catch-release and comes with one ten round magazine.

The SPR-308's Quattro Alloy Tactical forend features a heat vented design, with M-LOK accessory attachment locations for MIL-STD 1913 accessory rails at 3, and 9 o'clock positions and at 6 o'clock for bipod/tripod attachment. The SPR-308 also features Ashbury's patented, continuous one-piece unitized MIL-STD 1913 20 MOA monolithic scope rail. The patented monolithic rail provides a secure rifle scope mount, reduces vibration, and increases structural rigidity for long range accuracy, and in-line attachment of clip-on night vision and thermal weapon sights.

Ergonomic adjustability, modularity, shoot-ability, and low-felt recoil with ½ MOA precision are all hallmarks of the SPR-308 Precision Tactical Rifle.



Trusted to Make it Better!

Shown with Optional Accessories

## CALIBER

.308 Winchester (*optional 7.62 x 51mm*)

## ACTION

SABER SX Short Action Octagonal Receiver, 4140 Chromoly, Steel Black Nitride Finish (*optional left hand model*)

## BOLT

One-Piece Fluted Two-Lug 4140 Tool Steel, Mini-16 Extractor, Caliber Engraved Bolt, Black Nitride Finish

## TRIGGER

Single-Stage Adjustable Trigger Tech Trigger (*set to 3.5 lbs. / 1.5 kg*) (*optional 2-stage adjustable trigger*)

## BARREL

- 20" Standard (*optional 24" and 16.5" ASW Contour*)
- Pinnacle™ Series 416R Stainless Steel, Fluted Match Grade, Cut Rifling Hand Lapped, 1-in-10 Twist - Target Crown 11°, Muzzle Threaded 5/8-24

## MUZZLE BRAKE

AAC Blackout 51T (*alternate manufacturer and models available*)

## SOUND SUPPRESSOR (*optional*)

AAC 762SD (*alternate manufacturer and models available*)

## RIFLE CHASSIS - MODULAR

SABER ASX-A3 Alloy Tactical (AL-T) MOD-1

## SHOULDER STOCK - ERGONOMICALLY ADJUSTABLE

PBA-H - Push Button Adjustable Hybrid, Tool-less Positive Locking

- Limbsaver Premium Recoil Pad
- Butt Hook, Interchangeable
- Flush Cup Sling Swivel Sockets x2
- Monopod, 3-Position (*optional*)

## STOCK INTERFACE

Double Locking Hinge, Tension Adjustable

## MAGAZINE - BOX

- 10rd Polymer Magazine (x1)
- 5rd Steel and 5rd Polymer Magazines (*optional*)

## HAND GRIP

Ergo Grip Slimline (*Changeable M16/M4 Style*)

## GRIP ANGLE ADAPTERS

11° (*optional 17.5° and 27° - user installed*)

## FOREND

- Quattro Alloy Tactical with M-LOK Accessory Attachment System for MIL-STD 1913 Accessory Rail Locations 3-6-9 o'clock
- Flush Cup Sling Swivel Socket (x2)

## MONOLITHIC PICATINNY SCOPE BASE RAIL

20 MOA Forward Sloping, One-Piece In-line Day & Night Optics

## ACCESSORY RAILS

M-LOK 7-Slot Accessory Rails (x3)

## SURFACE COATINGS

- Black Nitride Action and Barrel & Cerakote Ceramic Finish
- MIL-STD 810G Compliant Corrosion & Chemical Resistance

## COLOR

- SABER Chassis: Armor Black
- Barreled Action: Armor Black

## ACCURACY

½ MOA 5-Shot Group 175Gr BTHP Match-Grade Ammunition

## PACKAGING

- Heavy Duty Corrugated Shipping Container
- Hard Lockable Transit Case with Custom Foam Interior (*optional*)
- Nylon Padded Field Carry Bag (*optional*)

## BASE RIFLE WEIGHT & DIMENSIONS (*approx*)

- 12.9 lbs. / 5.9 kg (with empty 10rd magazine)
- 14.6 lbs. / 6.6 kg (with empty 10rd magazine, scope & rings)
- Extended Length 45.5" / Folded Length 35.5" / Thickness 5.4"

Specifications are Subject to Change. Custom Configurations Available.

Utility & Design Patents at  
APO-Patents.com



# SPR-308 PRECISION RIFLE BALLISTICS & ACCESSORIES

SABER-Precision-Rifle.com

SABER® Precision Rifle - Tactical System

## EXTERNAL BALLISTICS

.308 Winchester 175gr Match 2600fps .547BC

Distance		Elevation	Elevation	Velocity
Yards	Meters	MOA	MILS	FPS
100	91	0	0	2434
200	183	1.25	0.4	2274
300	271	3.75	1.1	2120
400	366	7.00	2.0	1970
500	457	10.50	3.1	1826
600	549	14.50	4.2	1688
700	640	19.25	5.6	1555
800	732	24.25	7.1	1428
900	823	30.00	8.8	1307
1000	914	36.75	10.7	1197
1100	1006	44.25	12.8	1107

Baro Pressure:	29.53 in. Hg.	Caliber:	.308 Winchester	Bullet Weight:	175gr
Humidity:	78%	Bullet Type:	BTHP Open Tip Match	Ballistic Coefficient:	0.547 (G1)
Temperature:	59°	Velocity:	2600± Feet Per Second	Rifle:	SPR-308 20" BBL
Elevation:	0ft ASL				

Standard Metro Atmospheric Conditions

## ACCESSORIES

- Premium Rifle Scopes
- SABER EO Scope Rings
- Field Monopod
- Bipod
- Shooting Sling
- Sound Suppressor
- Precision Rifle Cleaning Kit
- Protective Field Nylon Padded Bag
- Custom Transit Case Foam Insert
- Ballistic Software & Handheld Computer
- Spare Steel/Polymer Magazines
- SABER Field Multi-Tool
- Anti-Cant Device, Scope Mounted
- Angle Cosine Indicator (ACI)
- Field Density Altitude Ballistic Calculator (.308Win)
- Spare Fasteners Package
- Repair Parts Kit
- Sniper's Field Tool Kit
- Spotting Scope / TACT 3 Tripod Kit
- RSTA-II Tripod Shooting System

Contact us for Complete Rifle Packages, Match-grade Ammunition, Armorer & Precision Rifle Marksmanship Training

## COATINGS & FINISHES



Other Colors & Coatings Available



**APO**  
ASHBURY PRECISION ORDNANCE  
The Precision Long Range Rifle Specialists



Made in USA

Ashbury Precision Ordnance Mfg. • 84 Business Park Circle • Ruckersville • Virginia • 22968 • 434-296-8600  
AshburyPrecisionOrdnance.com • info@AshburyPrecisionOrdnance.com



Scan me