

8

WARRIDR® ASYMMETRIC

ASW-308WIN PRECISION TACTICAL RIFLE BALLISTICS **R1** ACCESSORIES

Asymmetric-Warrior.com

EXTERNAL BALLISTICS

308 Winch	.308 Winchester 175gr Match 2600fps .547BC	atch 2600fps	5.547BC		
Distance	Ince	Elevation	Elevation		Velocity
Yards	Meters	MOA	MILS	S	FPS
100	91	0	0		2434
200	183	1.25	0.4		2274
300	271	3.75	1.1		2120
400	366	7.00	2.0		1970
500	457	10.50	3.1		1826
600	549	14.50	4.2		1688
700	640	19.25	5.6		1555
800	732	24.25	7.1		1428
006	823	30.00	8.8		1307
1000	914	36.75	10.7		1197
1100	1006	44.25	12.8		1107
Station Pressure: 29.53 in. Hg. Humidity: 78% Temperature: 59°	: 29.53 in. Hg. 78% 59°	Caliber: Bullet Type: Velocity:	.308 Winchester BTHP Open Tip Match 2600± Feet Per Second	Bullet Weight: 175gr Ballistic Coefficient: 0.547 (G1) Rifle: ASW-308 2	175gr ent: 0.547 (G1) ASW-308 20" BBL

ACCESSORIES

ASYMMETRIC WARRIOR® Precision Tactical Rifle System

- Field Monopod Premium Rifle Scopes
 SABER EO Scope Rings
- Bipod

Anti-Cant Device, Scope Mounted
Angle Cosine Indicator (ACI)

Spare Steel/Polymer Magazines
SABER Field Multi-Tool

Field Density Altitude Ballistic

- Shooting Sling
- Sound SuppressorPrecision Rifle Cleaning Kit
- Protective Field Nylon Padded Bag
 Custom Transit Case Foam Insert
- Ballistic Software & Handheld
 Computer
- Spotting Scope / TACT 3 Tripod Kit
 RSTA-II Tripod Shooting System

Repair Parts Kit
Sniper's Field Tool Kit

Spare Fasteners Package

Calculator (.308Win)

- jes, Match

COATINGS & FINISHES



le in USA The alists



Ashbury Precision Ordnance Mfg. • 84 Business Park Circle • Ruckersville • Virginia • 22968 • 434-296-8600 AshburyPrecisionOrdnance.com • info@AshburyPrecisionOrdnance.com



PRECISION TACTICAL RIFLE SYSTEM

Patented Modularity by Definition... Precision Engineered by Design

ASW-308WIN

Asymmetric-Warrior.com

ASYMMETRIC WARRIOR® Precision Tactical Rifle System

The Asymmetric Warrior[®] ASW-308 Precision Tactical Rifle is Ashbury Precision Ordnance's premium, custom crafted, long range, precision rifle. The full featured ASW-308 is designed to provide users with a rugged, modular and ergonomically adjustable precision rifle designed for years of reliable service under tough field conditions. Chambered for the proven 308 Winchester cartridge, the ASW-308 provides exceptional accuracy and is capable of precision target engagements to distances greater than 800 yards.

Designed for intermediate range precision shooting and dependability in the field, the ASW-308 provides users with many noteworthy operational features. *The Action:* APO's SABER® *SX* octagonal stainless steel bolt action receiver is precision CNC manufactured to close tolerances with a one-piece bolt crafted of tool steel, finished with a tough Black Nitride coating. *The Barrel:* Pinnacle Series 416R stainless steel – ASW fluted contour - match grade, threaded muzzle, and highly efficient muzzle brake suppressor adapter. *The Trigger:* Adjustable two-stage trigger with a reliable light first stage & second stage that breaks crisply at 3 lbs.

The Patented SABER Chassis: SABER ASX MOD-1 Carbon Fiber Series modular rifle chassis system. SABER rifle chassis are rugged, reconfigurable, low maintenance, and require no bedding to deliver optimal accuracy. SABER rifle chassis are impervious to foul weather conditions, and hot/cold temperature extremes. *The Ergonomic Shoulder Stock:* Tool-less ergonomically adjustable PBA-H (Push Button Adjustable Hybrid) shoulder stock. The PBA-H provides push button length of pull, vertical recoil pad drop and thumbscrew cheek piece height adjustment - all positive locking and *completely tool-less*! The PBA-H utilizes a butt hook for non-shooting hand support, and an optional rapidly adjustable 3-position field monopod is available.

The ASW-308 has a user adjustable hand grip to customize the distance-to-trigger for large and small hands and an interchangeable near vertical 11° grip angle. The ASW-308 is fitted with an ambidextrous paddle lever magazine catch-release & comes with one ten round magazine in the A3 configuration.

The ASW-308's Quattro Carbon Fiber MOD-1 forend has a unique heat/mirage mitigating design, exclusive "co-bore aligned" accessory rail locations at 3, and 9 o'clock positions and a 6 o'clock rail for bipod attachment. The ASW-308 also features Ashbury's patented, continuous one-piece unitized MIL-STD 1913 20 MOA monolithic scope rail. The patented monolithic rail provides a secure rifle scope mount, reduces vibration, and increases structural rigidity for long range accuracy, and in-line attachment of clip-on night vision and thermal devices.

Ergonomic adjustability, modularity, shoot-ability, and low-felt recoil with ½ MOA precision are all hallmarks of the ASW-308 Precision Tactical Rifle.







CALIBER

.308 Winchester (optional 7.62 x 51mm)

ACTION

SABER SX Short Action Octagonal Receiver, 416R Stainless Steel, Black Nitride Finish (optional left hand)

BOLT

One-Piece Fluted Two-Lug 4140 Tool Steel, Mini-16 Extractor, Caliber Engraved Bolt, Black Nitride Finish

TRIGGER

Two-Stage Adjustable with Curved/Straight Trigger Face (set to 3 lbs.)

BARREL

- 27" ASW Contour and 20" K1 Contour
- Pinnacle[™] Series 416R Stainless Steel, Fluted Match Grade, Cut Rifling Hand Lapped - 1:9.4 Twist - Target Crown 11^o, Muzzle Threaded 3/4-24

MUZZLE BRAKE

AAC Blackout 51T (alternate manufacturer and models available)

SOUND SUPPRESSOR (optional) AAC 762SD (alternate manufacturer and models available)

RIFLE CHASSIS - MODULAR

SABER ASX-A3 Carbon Fiber MOD-1

SHOULDER STOCK - ERGONOMIC/ADJUSTABLE

PBA-H - Push Button Adjustable Hybrid, Tool-less Positive Locking

- Limbsaver Premium Recoil Pad
- Flush Cup Sling Swivel Sockets x2
 Monopod, 3-Position (optional)

STOCK INTERFACE

Folding Lockable Stainless Steel Hinge (optional Fixed & Double Locking)

Butt Hook, Interchangeable

MAGAZINE - BOX

- A3 -10rd Steel Magazine (x1)
- 5rd Steel and 5 or 10rd Polymer Magazines (optional)

HAND GRIP

Ergo Grip Slimline (Changeable AR-15/M-16 Style)

GRIP ANGLE ADAPTERS

11° (optional 17.5° and 27°)

FOREND

- Quattro Carbon Fiber Series, Co-Bore Aligned Accessory Rail Locations 3-6-9-12 o'clock
- Flush Cup Sling Swivel Socket (x3)

MONOLITHIC PICATINNY SCOPE RAIL

20 MOA Slant Co-Linear Mounted Day & Night Optics

ACCESSORY RAILS

- 12" Picatinny Rail with Flushcup Sockets (x1)
- 12" Picatinny Rail (x2)
- 4" Picatinny Accessory Rail with Flushcup Sockets (optional)

SURFACE COATINGS

Hard Coat Anodized and Cerakote Coating

COLOR

- Forend: Natural Black Carbon Fiber
- SABER Chassis: Black MIL -A-8625 Type III Hard Coat Anodized
- Barreled Action: Armor Black

ACCURACY

1/2 MOA 5-Shot Group 175Gr BTHP Target/Match-Grade Ammunition

PACKAGING

- Heavy Duty Corrugated Shipping Container
- Hard Lockable Transit Case with Custom Foam Interior (optional)
- Nylon padded Field Carry Bag (optional)

BASE RIFLE WEIGHT & DIMENSIONS

12.5 lbs. / Extended Length 41.5" / Folded Length 31.5" (approx)

Specifications are Subject to Change. Custom Configurations Available.