

M783E-MSV



WARRIOR®  
SYSTEMS

ASW-338LM BALLISTICS & ACCESSORIES

Asymmetric-Warrior.com

ASYMMETRIC WARRIOR® Precision Tactical Rifle System

.338LM EXTERNAL BALLISTICS

300gr Match 2739fps .831BC (G1)

Distance		Elevation	Elevation	Velocity
Yards	Meters	MOA	MILS	FPS
0	0	0	0.0	2739
200	183	1.00	0.2	2516
400	366	5.25	1.6	2303
600	549	11.00	3.2	2099
800	732	17.50	5.1	1904
1000	914	25.25	7.4	1719
1200	1097	34.00	9.9	1544
1400	1280	44.50	12.9	1377
1600	1463	55.50	16.4	1226
1800	1645	70.75	20.6	1104
2000	1828	87.75	25.5	1019

Station Pressure: 29.53 in. Hg.	Caliber: .338LM / 8.6 x 70mm	Bullet Weight: 300 grain
Humidity: 78%	BTHP Open Tip Match	Ballistic Coefficient: 0.831 (G1)
Temperature: 59° F / 15° C	Velocity: 2739± Feet Per Second	Rifle: ASW-338LM
Elevation: 0 ft ASL		Barrel Length: 27"

Standard Metro Atmospheric Conditions

PRECISION TACTICAL RIFLES ACCESSORIES

- Premium Rifle Scopes
  - SABER EO Scope Rings
  - Field Monopod - 3 Position
  - Bipod
  - Shooting Sling
  - Sound Suppressor
  - Precision Rifle Cleaning Kit
  - Protective Field Nylon Padded Bag
  - Custom Transit Case Foam Insert
  - Ballistic Software & Handheld Computer
- Spare Steel Magazines
  - SABER Field Multi-Tool
  - Anti-Cant Device, Scope Mounted
  - Angle Cosine Indicator (ACI)
  - Field Density Altitude Ballistic Calculator (.338LM)
  - Repair & Spare Parts Kit
  - Sniper's Field Tool Kit
  - Spotting Scope / TACT 3 Tripod Kit
  - RSTA-II Tripod Shooting System

Contact us for Complete Rifle Packages, Match-grade Ammunition, Armor & Precision Rifle Marksmanship Training

COATINGS & FINISHES



Other Colors & Coatings Available



Made in USA



v20190204

Ashbury Precision Ordnance Mfg. • 84 Business Park Circle • Ruckersville • Virginia • 22968 • 434-296-8600  
AshburyPrecisionOrdnance.com • info@AshburyPrecisionOrdnance.com



Scan me



# ASW-338LM

Asymmetric-Warrior.com

ASYMMETRIC WARRIOR® Precision Tactical Rifle System

The Asymmetric Warrior® ASW-338LM Precision Tactical Rifle is Ashbury Precision Ordnance’s premium, custom crafted, extreme long range, precision rifle. The full featured ASW-338LM is designed to provide users with a rugged, modular and ergonomically adjustable precision rifle designed for years of reliable service under tough field conditions. Chambered for the powerful .338 Lapua Magnum cartridge, the ASW-338LM provides exceptional accuracy and is capable of precision target engagements to distances greater than 1,700+ yards.

Designed for extreme long range precision shooting and dependability in the field, the ASW-338LM provides users with many operational features. **The Action:** APO’s SABER® EX octagonal stainless steel bolt action receiver is precision CNC manufactured to close tolerances with a one-piece bolt crafted of tool steel, finished with a tough Black Nitride coating. **The Barrel:** Pinnacle Series 416R stainless steel – ASW fluted contour - match grade, threaded muzzle, and highly efficient muzzle brake suppressor adapter. **The Trigger:** Adjustable two-stage trigger with a reliable light first stage & second stage that breaks crisply at 3 lbs.

**The Patented SABER Chassis:** SABER AEX MOD-1 Carbon Fiber Series modular rifle chassis system. SABER rifle chassis are rugged, reconfigurable, low maintenance, and require no bedding to deliver optimal accuracy. SABER rifle chassis are impervious to foul weather conditions, and hot/cold temperature extremes. **The Ergonomic Shoulder Stock:** Tool-less ergonomically adjustable PBA-H (Push Button Adjustable Hybrid) shoulder stock. The PBA-H provides push button length of pull, vertical recoil pad drop and thumbscrew cheek piece height adjustment - all positive locking and *completely tool-less!* The PBA-H utilizes a butt hook for non-shooting hand support, and an optional rapidly adjustable 3-position field monopod is available.

The ASW-338LM has a user adjustable hand grip to customize the distance-to-trigger for large and small hands and an interchangeable near vertical 11° grip angle. The ASW-338LM is fitted with an ambidextrous paddle lever magazine catch-release & comes with one five round magazine in the A1 configuration or 10rd magazine in the A2 configuration.

The ASW-338LM’s Quattro Carbon Fiber MOD-1 forend has a unique heat/mirage mitigating design, exclusive “co-bore aligned” accessory rail locations at 3, and 9 o’clock positions and a 6 o’clock rail for bipod attachment. The ASW-338LM also features Ashbury’s patented, continuous one-piece unitized MIL-STD 1913 30 MOA monolithic scope rail. The patented monolithic rail provides a secure rifle scope mount, reduces vibration, and increases structural rigidity for long range accuracy, and in-line attachment of clip-on night vision and thermal devices.

Ergonomic adjustability, modularity, shoot-ability, and low-felt recoil with ½ MOA precision are all hallmarks of the ASW-338LM Precision Tactical Rifle.



ASW-338LM\_27A2 10rd Magazine Configuration with Optional Accessories

NSN 1005-01-631-1508



Trusted to Make it Better!



Utility & Design Patents at APO-Patents.com

## CALIBER

.338 Lapua Magnum (8.6 x 70mm)

## ACTION

SABER EX Magnum Octagonal Receiver, 416R Stainless Steel, Black Nitride Finish (*optional left hand*)

## BOLT

One-Piece Fluted Two-Lug 4140 Tool Steel, Mini-16 Extractor, Caliber Engraved Bolt, Black Nitride Finish

## TRIGGER

Two-Stage Adjustable with Dual Curved/Straight Trigger (*set to ±3 lbs.*)

## BARREL

- 27” ASW Contour and 20” K1 Contour
- Pinnacle™ Series 416R Stainless Steel, Fluted Match Grade, Cut Rifling Hand Lapped - 1:9.4 Twist - Target Crown 11°, Muzzle Threaded 3/4-24

## MUZZLE BRAKE

AAC Blackout 90T (*alternate options available*)

## SOUND SUPPRESSOR (*optional*)

AAC TITAN QD Titanium

## RIFLE CHASSIS - MODULAR

- SABER AEX-A1 Carbon Fiber MOD-1
- SABER AEX-A2 Carbon Fiber MOD-1 (*optional*)

## SHOULDER STOCK - ERGONOMIC/ADJUSTABLE

PBA-H - Push Button Adjustable Hybrid, Tool-less Positive Locking

- Limbsaver Premium Recoil Pad
- Butt Hook, Interchangeable
- Flush Cup Sling Swivel Sockets x2
- Monopod, 3-Position (*optional*)

## STOCK INTERFACE

Folding Lockable Stainless Steel Hinge (*optional Fixed & Double Locking*)

## MAGAZINE - BOX

- A1 -5rd CIP Magazine 3.850” (x1)
- A2 - 10rd CIP Magazine 3.76” (*optional*)

## HAND GRIP

Ergo Grip Slimline (*Changeable M4 Style*)

## GRIP ANGLE ADAPTERS

11° (*optional 17.5° and 27°*)

## FOREND

- Quattro Carbon Fiber Series, Co-Bore Aligned Accessory Rail Locations 3-6-9-12 o’clock
- Flush Cup Sling Swivel Socket (x3)

## MONOLITHIC PICATINNY SCOPE RAIL

30 MOA Slant Co-Linear Mounted Day & Night Optics

## ACCESSORY RAILS

- 12” Picatinny Rail with Flushcup Sockets (x1)
- 12” Picatinny Rail (x2)
- 4” Picatinny Accessory Rail with Flushcup Sockets (*optional*)

## SURFACE COATINGS

Hard Coat Anodized and Cerakote Coating

## COLOR

- Forend: Natural Black Carbon Fiber
- SABER Chassis: Black MIL -A-8625 Type III Hard Coat Anodized
- Barreled Action: Armor Black

## ACCURACY

½ MOA 5-Shot Group 250gr Target/Match-Grade Ammunition

## PACKAGING

- Heavy Duty Corrugated Shipping Container
- Hard Lockable Transit Case with Custom Foam Interior (*optional*)
- Nylon padded Field Carry Bag (*optional*)

## BASE RIFLE WEIGHT & DIMENSIONS (MBS Only - No Suppressor)

- 27” Model 16 lbs / Overall Length 49.5” / Folded Length 40.5” (*approx*)
- 20” Model 14.5 lbs / Overall Length 42.5” / Folded Length 33.5” (*approx*)

Specifications are Subject to Change. Custom Configurations Available.