

# ASYMMETRIC WARRIOR®



The Precision Long Range Rifle Specialists



## ASW-308WIN

LONG RANGE

PRECISION TACTICAL RIFLE SYSTEM

Patented Modularity by Definition... Precision Engineered by Design



# ASW-308WIN

Asymmetric-Warrior.com

ASYMMETRIC WARRIOR® Precision Tactical Rifle System

The Asymmetric Warrior® ASW-308 Precision Tactical Rifle is Ashbury Precision Ordnance’s premium, custom crafted, long range, precision rifle. The full featured ASW-308 is designed to provide users with a rugged, modular and ergonomically adjustable precision rifle designed for years of reliable service under tough field conditions. Chambered for the proven 308 Winchester cartridge, the ASW-308 provides exceptional accuracy and is capable of precision target engagements to distances greater than 800 yards.

Designed for intermediate range precision shooting and dependability in the field, the ASW-308 provides users with many noteworthy operational features. **The Action:** APO’s SABER® SX octagonal stainless steel bolt action receiver is precision CNC manufactured to close tolerances with a one-piece bolt crafted of tool steel, finished with a tough Black Nitride coating. **The Barrel:** Pinnacle Series 416R stainless steel – ASW fluted contour - match grade, threaded muzzle, and highly efficient muzzle brake suppressor adapter. **The Trigger:** Adjustable two-stage trigger with a reliable light first stage & second stage that breaks crisply at 3 lbs.

**The Patented SABER Chassis:** SABER ASX MOD-1 Carbon Fiber Series modular rifle chassis system. SABER rifle chassis are rugged, reconfigurable, low maintenance, and require no bedding to deliver optimal accuracy. SABER rifle chassis are impervious to foul weather conditions, and hot/cold temperature extremes. **The Ergonomic Shoulder Stock:** Tool-less ergonomically adjustable PBA-H (Push Button Adjustable Hybrid) shoulder stock. The PBA-H provides push button length of pull, vertical recoil pad drop and thumbscrew cheek piece height adjustment - all positive locking and *completely tool-less!* The PBA-H utilizes a butt hook for non-shooting hand support, and an optional rapidly adjustable 3-position field monopod is available.

The ASW-308 has a user adjustable hand grip to customize the distance-to-trigger for large and small hands and an interchangeable near vertical 11° grip angle. The ASW-308 is fitted with an ambidextrous paddle lever magazine catch-release & comes with one ten round magazine in the A3 configuration.

The ASW-308’s Quattro Carbon Fiber MOD-1 forend has a unique heat/mirage mitigating design, exclusive “co-bore aligned” accessory rail locations at 3, and 9 o’clock positions and a 6 o’clock rail for bipod attachment. The ASW-308 also features Ashbury’s patented, continuous one-piece unitized MIL-STD 1913 20 MOA monolithic scope rail. The patented monolithic rail provides a secure rifle scope mount, reduces vibration, and increases structural rigidity for long range accuracy, and in-line attachment of clip-on night vision and thermal devices.

Ergonomic adjustability, modularity, shoot-ability, and low-felt recoil with ½ MOA precision are all hallmarks of the ASW-308 Precision Tactical Rifle.felt recoil are hallmarks of the ASW-308 Precision Tactical Rifle.



Shown with Optional Accessories



Utility & Design Patents at  
APO-Patents.com



Trusted to Make it Better!

## CALIBER

.308 Winchester (optional 7.62 x 51mm)

## ACTION

SABER SX Short Action Octagonal Receiver, 416R Stainless Steel, Black Nitride Finish (optional left hand)

## BOLT

One-Piece Fluted Two-Lug 4140 Tool Steel, Mini-16 Extractor, Caliber Engraved Bolt, Black Nitride Finish

## TRIGGER

Two-Stage Adjustable with Curved/Straight Trigger Face (set to 3 lbs.)

## BARREL

- 27” ASW Contour and 20” K1 Contour
- Pinnacle™ Series 416R Stainless Steel, Fluted Match Grade, Cut Rifling Hand Lapped - 1:9.4 Twist - Target Crown 11°, Muzzle Threaded 3/4-24

## MUZZLE BRAKE

AAC Blackout 51T (alternate manufacturer and models available)

## SOUND SUPPRESSOR (optional)

AAC 762SD (alternate manufacturer and models available)

## RIFLE CHASSIS - MODULAR

SABER ASX-A3 Carbon Fiber MOD-1

## SHOULDER STOCK - ERGONOMIC/ADJUSTABLE

- PBA-H - Push Button Adjustable Hybrid, Tool-less Positive Locking
- Limbsaver Premium Recoil Pad
  - Butt Hook, Interchangeable
  - Flush Cup Sling Swivel Sockets x2
  - Monopod, 3-Position (optional)

## STOCK INTERFACE

Folding Lockable Stainless Steel Hinge (optional Fixed & Double Locking)

## MAGAZINE - BOX

- A3 -10rd Steel Magazine (x1)
- 5rd Steel and 5 or 10rd Polymer Magazines (optional)

## HAND GRIP

Ergo Grip Slimline (Changeable AR-15/M-16 Style)

## GRIP ANGLE ADAPTERS

11° (optional 17.5° and 27°)

## FOREND

- Quattro Carbon Fiber Series, Co-Bore Aligned Accessory Rail Locations 3-6-9-12 o'clock
- Flush Cup Sling Swivel Socket (x3)

## MONOLITHIC PICATINNY SCOPE RAIL

20 MOA Slant Co-Linear Mounted Day & Night Optics

## ACCESSORY RAILS

- 12” Picatinny Rail with Flushcup Sockets (x1)
- 12” Picatinny Rail (x2)
- 4” Picatinny Accessory Rail with Flushcup Sockets (optional)

## SURFACE COATINGS

Hard Coat Anodized and Cerakote Coating

## COLOR

- Forend: Natural Black Carbon Fiber
- SABER Chassis: Black MIL -A-8625 Type III Hard Coat Anodized
- Barreled Action: Armor Black

## ACCURACY

½ MOA 5-Shot Group 175Gr BTHP Target/Match-Grade Ammunition

## PACKAGING

- Heavy Duty Corrugated Shipping Container
- Hard Lockable Transit Case with Custom Foam Interior (optional)
- Nylon padded Field Carry Bag (optional)

## BASE RIFLE WEIGHT & DIMENSIONS

12.5 lbs. / Extended Length 41.5” / Folded Length 31.5” (approx)

Specifications are Subject to Change. Custom Configurations Available.



# ASW-308WIN Precision Tactical Rifle Ballistics & Accessories

Asymmetric-Warrior.com

ASYMMETRIC WARRIOR® Precision Tactical Rifle System

## EXTERNAL BALLISTICS

.308 Winchester 175gr Match 2600fps .547BC

Distance		Elevation	Elevation	Velocity
Yards	Meters	MOA	MILS	FPS
100	91	0	0	2434
200	183	1.25	0.4	2274
300	271	3.75	1.1	2120
400	366	7.00	2.0	1970
500	457	10.50	3.1	1826
600	549	14.50	4.2	1688
700	640	19.25	5.6	1555
800	732	24.25	7.1	1428
900	823	30.00	8.8	1307
1000	914	36.75	10.7	1197
1100	1006	44.25	12.8	1107

Station Pressure: 29.53 in. Hg.	Caliber: .308 Winchester	Bullet Weight: 175gr
Humidity: 78%	Bullet Type: BTHP Open Tip Match	Ballistic Coefficient: 0.547 (G1)
Temperature: 59°	Velocity: 2600± Feet Per Second	Rifle: ASW-308 20" BBL
Elevation: 0ft ASL		

Standard Metro Atmospheric Conditions

## ACCESSORIES

- Premium Rifle Scopes
- SABER EO Scope Rings
- Field Monopod
- Bipod
- Shooting Sling
- Sound Suppressor
- Precision Rifle Cleaning Kit
- Protective Field Nylon Padded Bag
- Custom Transit Case Foam Insert
- Ballistic Software & Handheld Computer
- Spare Steel/Polymer Magazines
- SABER Field Multi-Tool
- Anti-Cant Device, Scope Mounted
- Angle Cosine Indicator (ACI)
- Field Density Altitude Ballistic Calculator (.308Win)
- Spare Fasteners Package
- Repair Parts Kit
- Sniper's Field Tool Kit
- Spotting Scope / TACT 3 Tripod Kit
- RSTA-II Tripod Shooting System

Contact us for Complete Rifle Packages, Match-grade Ammunition, Armorer & Precision Rifle Marksmanship Training

## COATINGS & FINISHES



Other Colors & Coatings Available



Made in USA

**APO**  
ASHBURY PRECISION ORDNANCE  
The Precision Long Range Rifle Specialists

Ashbury Precision Ordnance Mfg. • 84 Business Park Circle • Ruckersville • Virginia • 22968 • 434-296-8600  
AshburyPrecisionOrdnance.com • info@AshburyPrecisionOrdnance.com

Scan Me!

